



Precision Rated Optics

Work with a PRO!

200 Series *Tri Light Sources*

3-Year Warranty!



LS-201T Light Source

Offering excellent stability and portability for accurate fiber optic testing, the LS-202T provides stable laser power at 1310, 1550 and 1625nm wavelengths. This compact unit will operate in either continuous wave (CW) mode or modulated mode.

Output power is instantly adjustable from the keypad. A convenient "Low-Battery" indicator reminds the user to recharge the battery, while the lightweight and smaller size of the LS-202T delivers rock-solid reliability under all working conditions.

The LS-202T is sold, serviced and supported in the USA, comes standard with FC/PC, SC/PC and ST/PC adaptors, and is backed by PRO's legendary 3-Year manufacturer's warranty.

- Easy-to-use, Straight Forward Operation
- LCD Backlight for Easy Operation in Darker Environments
- Rechargeable Batteries Included
- Three-Year Warranty and Recommended Calibration Interval
- Sold, Serviced and Supported in the USA

SPECIFICATIONS

Output wavelength (nm)	1310/ 1550/ 1625
Emitter Type	LD
Connectors	FC/PC, SC/PC, ST/PC (APC is Available at the Time of Ordering)
Output Stability	Short-Term (15 min.): $\pm 0.05\text{dB}$ @ 1310,1550nm; $\pm 0.1\text{dB}$ @ 1625nm Long-Term (8 Hours): $\pm 0.1\text{dB}$ @ 1310,1550nm; $\pm 0.2\text{dB}$ @ 1625nm
Central Wavelength	1310 (± 20) & 1490 (± 20) & 1550 (± 20)
Spectral Width	5 nm
Output Frequency (Hz)	270 / 1,000 / 2,000
Output Power	-5 dBm
Power Supply	2500mAh Ni-MH AA (x2), AC/DC Power
Operating Temperature	14° F ~ 122° F (-10° C ~ 50° C)
Storage Temperature	-4° F ~ 158° F (-20° C ~ 70° C)
Weight & Dimensions (HxWxD)	6.3" x 3" x 1.8" / 9.5 oz (160 x 76 x 45 mm / 270 g)

LS-202T Light Sources Standard Package Includes:

Light Source, FC/PC, SC/PC, ST/PC Interchangeable Connector, User Manual, Worldwide-Compatible AC/DC Power Adaptor, Rechargeable Ni-MH Batteries (x2), Test Report, Soft Carrying Case

Ordering Information

LS-202T	Light Source (FTTx) (1310/1550/1625)
---------	--------------------------------------