



Precision Rated Optics

Work with a PRO!

OFS-947S Fusion Splicer



- Core Alignment Splicing Method with DACAS (Digital Analysis Core Alignment System)
- The World's Highest Magnification and Resolution
- 5" Color LCD Touch Screen
- Detachable SOC Holder and Heating Oven
- 3 Bright LEDs and Illuminated Keypads for Dark Environment
- Ceramic Clamp for Improved Durability
- Harsh Weather Conditions Adaptability

The OFS-947S is a core-alignment splicer with the world's highest fiber image magnification rate, is the most powerful and innovative fusion splicer in the market. Installed with a 5 inch high-resolution color LCD touch screen with user-friendly intuitive GUI (Graphic User Interface) offers large and clear fiber images to users. By double-tapping the screen, users can zoom in & out the image to the world's highest magnification of 520x. The OFS-947S offers maximum work efficiency through the fast heating time of 13s and the ultra-high battery capacity of 355 splice/heat cycles. Moreover, the 3 LED lights provide bright splice condition to the users working under dark environments. The OFS-947S offers the most reliable work experiences to our valuable customers.

SPECIFICATIONS

Applicable fiber type	SM(ITU-T G.652&G.657) / MM(ITU-T G.651) / DS(ITU-T G.653) / NZDS(ITU-T G.655)
Fiber count	Single
Applicable fiber cables	0.25mm- 3.0mm/ Indoor Cable
Applicable fiber diameter	Cladding diameter: 80-150µm Coating diameter: 125-1000µm
Splice loss	SM : 0.02dB, MM : 0.01dB, DS : 0.04dB, NZDS : 0.04dB, G.657 : 0.02dB
Splice mode	128 splice modes
Internal splice data storage	2000
Splicing time	SM Quick mode: 7s
Heat oven	20mm, 30mm, 40mm, 50mm, 60mm
Heating time	8- 900s
Typical heating time	13s
Heat mode	Various heat modes available
Displaying method	Two cameras and 5.0 inch color LCD monitor
Magnification	520x single X or Y view, or 520x both X and Y view
Tensile test	1.96-2.25N
Terminals	USB2.0 / MINI USB
Standard AC power voltage	AC 100-240V, 50-60Hz
Standard DC power voltage	DC 9-14V
Size (HxWxD)	6.57" x 5.62" x 6.41" in / 6.17lb (167 x 143 x 163mm / 2.8kg)
Operating condition	0~5000m above sea level, 0~95% relative humidity, 14~122°F (-10~50°C), 15m/s max wind speed
Storage condition	0~95% relative humidity, -40~176°F (-40~80°C)
Battery	-4~86°F (-20~30°C) for long time storage

OFS-947S Standard Package Includes:

Splicer, High Precision Cleaver, Fiber Holder, SOC Heater Cover, AC Adapter, Cooling Tray, Electrode, Electrode Grinder, Manual and/or download card, Battery Pack, Power Cable, USB Cable, Cigarette Lighter Cable, Carrying Case, Supplier's declaration of conformity, Test protocol

Ordering Information

OFS-947S	Fusion Splicer
----------	----------------