



User's Guide to the PM-12A Mini Optical Power Meter



Description

PM-12A Pen type optical power meter has compact structure and stable performance, ensure high measuring precision of 850nm, 1300nm, 1310nm, 1490nm, 1550nm and 1625nm wavelengths. Use together with GS series optical source could accurately measure the loss of fiber, cable and other passive optical device.



Features

- Imported sensor head .
- 2.5mm universal interface(support FC/SC/ST connectors).
- Low power consumption , continuously work more than 80 hours .
- Linear optical power and logarithmic power display.
- Power remains indication. Relative value measurement function.
- Compact and portable design.

Specification

Type	PM-12A
Display Range	+10~-70dBm @1550nm
Resolution(dB)	0.01
Calibrated Wavelength(nm)	850/1300/1310/1550/1490/1625
Sensor Type	InGaAs
Accuracy ^①	0.35dB ±1nW
Working Wavelength(nm)	800~1700
Continuous Working Hours ^②	About 80 hours(stand-by time: About 1600hours)
Power Source	Operates with two AAA batteries
Working Temp	-0~+40°C; <90%RH
Storage Temp	-20~+70°C; <90%RH
Accessory	2 pieces of AAA batteries, Quick guide, Packing box, Carrying case
Dimension	L120mm*W33mm*H30mm / About70g

Note:

- ① With 1550nm mode, under 23°C±3°C test condition
- ② New battery, under 23°C±3°C test condition

Control Panel



4

Num.	Icon	Description
1	850/1300/1310/ 1490/1550/1625nm	Display current wave length
2	-51.99dBm	Display current power value
3		Indicate remaining capacity of batteries
4		Power Switch: long press($\geq 2s$) to turn on/off the power; short press($\leq 1.5s$) to turn on/off backlight
5		Fn button: short press($\leq 1.5s$) to switch between wavelengths long pres($\geq 2s$) to set reference value
6	Interface	2.5mm standard interface
7	Dust Cap	Resist dust for interface
8	Battery Compartments	Install with 2*AAA batteries

5



Precision Rated Optics
1450 Greenwich St. Suite #303
San Francisco CA 94109
Phone number: 415-738-3476